

SoundStation® IP 7000

SIP-Based IP Conference Phone

Astounding voice quality and clarity from the world's most advanced IP conference phone



The Polycom® SoundStation® IP 7000 is a breakthrough conference phone that delivers outstanding performance and a robust feature set for SIP-based VoIP platforms. It is the most advanced conference phone ever developed, and is ideal for executive offices, conference rooms, and boardrooms.

The SoundStation IP 7000 features Polycom® HD Voice™ technology, boosting productivity and reducing listener fatigue by turning ordinary conference calls into crystal-clear interactive conversations. It delivers high-fidelity audio from 160 Hz to 22 kHz, capturing both the deeper lows and higher frequencies of the human voice for conference calls that sound as natural as being there.

For all conference calls, the SoundStation IP 7000 delivers advanced audio performance that far exceeds previous generations of conference phones. From full-duplex technology that eliminates distracting dropouts to the latest echo cancellation advancements, only Polycom can deliver a conference phone experience with no compromises.

The SoundStation IP 7000 is the most flexible and expandable conference phone ever developed. Connect two units together for increased loudness and microphone pickup, as well as multiple call control interfaces in the conference room. Connect up to two optional expansion microphones to a single phone to ensure close proximity for everyone in the room.

In the SoundStation IP 7000, Polycom has combined its rich history in voice conferencing and VoIP technology to develop a groundbreaking new conference phone that is the clear choice for SIP-enabled environments. It shares the same SIP phone software with Polycom's award-winning Polycom® SoundPoint® IP desktop phones—the most comprehensive, reliable and feature-rich SIP products in the industry.

Benefits

- Polycom® HD Voice™
 unparalleled clarity to make your
 conference calls more efficient
 and productive
- Polycom® Acoustic Clarity™ technology—delivers the best conference phone experience with no compromises
- Flexible configuration options—
 multi-unit connectivity,
 expansion microphones and
 integration with Polycom HDX
 room telepresence solutions to
 meet the needs of many different
 types of rooms
- Strong, robust SIP software leverages the most advanced SIP endpoint software in the industry, with advanced call handing, security, and provisioning features

Additional Polycom SoundStation IP 7000 features/benefits

- Equipped with built-in Power over Ethernet (PoE). An optional A/C power kit also available.
- 20 ft (6.1 m) microphone pickup, and even more with optional expansion microphones or multi-unit connectivity, reaching all corners of the room.
- Automatic Gain Control intelligently adjusts the microphone sensitivity based on where participants are seated in the conference room.
- Features technology that resists interference from mobile phones and other wireless devices, delivering clear communications without distractions.

SoundStation® IP 7000

POWER

- IEEE 802.3af Power over Ethernet (built in)
- Optional external universal AC power supply kit: 100-240V, 1.3A, 48V/50W

DISPLAY

- Size (W x H): 255 x 128 pixels
- White LED backlight with custom intensity control

KEYPAD

- Standard 12-key keypad
- Context-dependent soft keys: 4
- On-hook/Off-hook, redial, mute, volume up/down
- Directional navigation wheel

AUDIO FEATURES

- Loudspeaker
 - -- Frequency: 160-22,000 Hz
 - -- Volume: Adjustable to 88 dB at 1/2 meter peak volume
- Full-duplex: Type 1 compliant with IEEE 1329 full duplex standards
- Individual volume settings with visual feedback for each audio path
- Acoustic echo cancellation
- Background noise suppression

CALL HANDLING FEATURES

- Busy Lamp Field (BLF)
- Distinctive incoming call treatment / call waiting
- Call timer
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way conferencing
- One-touch speed dial, redial
- Call waiting
- Automatic off-hook call placement
- Do not disturb function

OTHER FEATURES

- Local feature-rich GUI
- Time and date display
- User-configurable contact directory and call history (missed, placed, and received)
- Customizable call progress tones
- Unicode UTF-8 character support.
 Multilingual user interface encompassing Chinese, Danish, Dutch, English
 (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Spanish, Swedish

SAFETY

- UL60950-1
- IEC60950-1
- EN60950-1
- CE Mark
- CSA C22.2, No. 60950-1-03
- AS/NZS60950-1

EMC

- FCC (47 CFR Part 15) Class A
- ICES-003 Class A
- EN55022 Class A
- CISPR22 Class A
- AS/NZS CISPR22 Class A
- VCCI Class A
- EN55024
- RoHS compliant

AC POWER VERSION SHIPS WITH:

- Telephone console
- 25 ft (7.6 m) Ethernet cable
- Universal power supply
- 7 ft (2.1 m) region-specific power cord
- Power insertion cable

ENVIRONMENTAL CONDITIONS

- Operating temperature: 0 40°C (+32 – 104°F)
- Relative humidity: 20% 85% (noncondensing)
- Storage temperature: -30 +55°C (-22 -131°F)

PHONE DIMENSIONS

• 37.2 x 7.3 x 39.4 cm (14.6 x 2.9 x 15.5) (W x H x D)

PHONE CONSOLE WEIGHT

• 2.4 lb (1.08 kg)

BOX DIMENSIONS

• 43.3 x 13 x 48.4 cm (17.0 x 5.1 x 19.1 in) (W x H x D)

BOX WEIGHT

• 5.4 lb (2.43 kg)

COUNTRY OF ORIGIN

Thailand

WARRANTY

• One (1) year